



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sika® Primer-206 G+P

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent, Product is not intended for consumer use

### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire AL7 1BQ  
United Kingdom

Telephone : +44 (0)1707 394444

### 1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
**Sika® Primer-206 G+P**



Revision Date 10.12.2015

Version 2.3

Print Date 05.08.2016

	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H336	May cause drowsiness or dizziness.
Supplemental Hazard Statements	: EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	: <b>Prevention:</b>	
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P233	Keep container tightly closed.
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P285	In case of inadequate ventilation wear respiratory protection.
	<b>Response:</b>	
	P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Hazardous components which must be listed on the label:

- 205-500-4 ethyl acetate
- 28182-81-2 Hexamethylene-1,6-diisocyanate homopolymer
- 223-981-9 tris(p-isocyanatophenyl) thiophosphate
- 500-125-5 Isophorondiisocyanate homopolymer

**Additional Labelling:**

EUH204 Contains isocyanates. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous components**

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
ethyl acetate 141-78-6 205-500-4 01-2119475103-46-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 50 - <= 100

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Sika® Primer-206 G+P



Revision Date 10.12.2015

Version 2.3

Print Date 05.08.2016

Hexamethylene-1,6-diisocyanate homopolymer 28182-81-2 01-2119488934-20-XXXX Contains: hexamethylene-di-isocyanate <= 0,3 %	Acute Tox.4; H332 Skin Sens.1; H317 STOT SE3; H335	>= 5 - < 10
tris(p-isocyanatophenyl) thiophosphate 4151-51-3 223-981-9 01-2119948848-16-XXXX Contains: chlorobenzene <= 1 %	Acute Tox.4; H302	>= 5 - < 10
Isophorondiisocyanate homopolymer 53880-05-0 931-312-3 500-125-5 01-2119488734-24-XXXX Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate <= 0,49 %	Skin Sens.1; H317 STOT SE3; H335	>= 5 - < 10
Substances with a workplace exposure limit :		
n-butyl acetate 123-86-4 204-658-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336	>= 2,5 - < 5
2-methoxy-1-methylethyl acetate 108-65-6 203-603-9 01-2119475791-29-XXXX Contains: 2-methoxypropyl acetate <= 1 %	Flam. Liq.3; H226	>= 1 - < 2,5

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.



If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance  
Allergic reactions  
Excessive lachrymation  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.

Risks : irritant effects  
sensitising effects  
  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical  
  
Unsuitable extinguishing media : Water

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
  
Further information : Use water spray to cool unopened containers.



---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.



Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : No data available

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters *	Basis *
ethyl acetate	141-78-6	TWA	200 ppm	GB EH40
		STEL	400 ppm	GB EH40
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
		STEL	100 ppm 548 mg/m3	GB EH40

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	urinary diamine: 1µmol/mol creatinine (Urine)	Post task	GB EH40 BAT

**8.2 Exposure controls**

**Personal protective equipment**

Eye protection : Safety glasses with side-shields  
 Eye wash bottle with pure water



- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : black
- Odour : ester-like
- Odour Threshold : No data available
- Flash point : -4 °C
- Ignition temperature : 333 °C
- Lower explosion limit (Vol-%) : 2,1 %(V)

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sika® Primer-206 G+P**



Revision Date 10.12.2015

Version 2.3

Print Date 05.08.2016

Upper explosion limit (Vol-%) :	11,5 %(V)
Flammability (solid, gas) :	No data available
Oxidizing properties :	No data available
Auto-ignition temperature :	No data available
pH :	ca. 7
Melting point/range / Freezing point :	No data available
Boiling point/boiling range :	> 77 °C
Vapour pressure :	99,9915 hPa
Density :	ca. 1,02 g/cm <sup>3</sup> at 20 °C
Water solubility :	Note: insoluble
Partition coefficient: n-octanol/water :	No data available
Viscosity, dynamic :	No data available
Viscosity, kinematic :	> 7 mm <sup>2</sup> /s at 40 °C
Relative vapour density :	No data available
Evaporation rate :	No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

The product is chemically stable.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**





Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

###### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

###### **Hexamethylene-1,6-diisocyanate homopolymer:**

Acute oral toxicity : LD50 Oral (Rat): > 5.001 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

###### **tris(p-isocyanatophenyl) thiophosphate:**

Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg  
Remarks: see user defined free text

Acute inhalation toxicity : LC50 (Rat): 5,721 mg/l  
Exposure time: 4 h

###### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

###### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg



**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

**Product:**

Remarks: Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Causes serious eye irritation.

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Product:**

Remarks: May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Product:**

Germ cell mutagenicity- Assessment : No data available

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assessment : No data available

**Reproductive toxicity**

Not classified based on available information.

**Product:**

Reproductive toxicity - Assessment : No data available

No data available

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.



**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

**n-butyl acetate :**

Toxicity to algae : EC50: 647,7 mg/l, 72 h, Desmodesmus subspicatus (green algae)

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**12.6 Other adverse effects**

No data available

---

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with



soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### ADR

**14.1 UN number** : 1866  
**14.2 Description of the goods** : RESIN SOLUTION  
**14.3 Class** : 3  
**14.4 Packing group** : II  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (D/E)  
**14.5 Environmentally hazardous** : no

### IATA

**14.1 UN number** : 1866  
**14.2 Description of the goods** : Resin solution  
**14.3 Class** : 3  
**14.4 Packing group** : II  
Labels : 3  
**14.5 Environmentally hazardous** : no

### IMDG

**14.1 UN number** : 1866  
**14.2 Description of the goods** : RESIN SOLUTION  
**14.3 Class** : 3  
**14.4 Packing group** : II  
Labels : 3  
EmS Number 1 : F-E  
EmS Number 2 : S-E  
**14.5 Marine pollutant** : no

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

VOC-CH (VOCV) : 61,06 %

VOC-EU (solvent) : 61,15 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002  
Control of Substances Hazardous to Health Regulations 2002  
The Management of Health and Safety at Work Regulations 1999  
Health and Safety at Work Act 1974  
Environmental Protection Act 1990 & Subsidiary Regulations

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

---

## SECTION 16: Other information

#### Full text of H-Statements

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Sika® Primer-206 G+P



Revision Date 10.12.2015

Version 2.3

Print Date 05.08.2016

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !