

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: UDO CLEAR LACQUER BLANCO 500 ML

· Article number: ULCL500

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

· Application of the substance / the mixture Paint

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Capella Solutions Group

Second Avenue

Chatham

Kent

ME4 5 AU

*Tel:* +44 (0)1634 823900 *Fax:* +44 (0)1634 823909

Email: sales@capellasolutionsgroup.com

· Further information obtainable from: Department Product Safety

• 1.4 Emergency telephone number: Tel: +44(0) 1634 823900 (08.00 / 17.00)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

#### · Hazard pictograms





GHS02

GHS07

#### · Signal word Danger

#### · Hazard-determining components of labelling:

acetone

n-butyl acetate

butan-1-ol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

### · Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  Flam. Gas 1, H220  Press. Gas C, H280	20-25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate  Flam. Liq. 3, H226 STOT SE 3, H336	10-12.5%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane  Flam. Gas 1, H220  Press. Gas C, H280	5-10%

(Contd. on page 3)

(Contd. of page 1)

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

CAC. 100 65 6		ntd. of pag
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	5-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane  Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.5%
CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose  Flam. Sol. 1, H228	1-2.5%

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

(Contd. on page 4)

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

Ingr	edients with limit values that require monitoring at the workplace:	
67-6	4-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm	
	Long-term value: 1210 mg/m³, 500 ppm	
115-	10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m³, 500 ppm	
	Long-term value: 766 mg/m³, 400 ppm	
123-	86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m³, 150 ppm	
108-	65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
	Sk	
106-	97-8 butane	
WEL	Short-term value: 1810 mg/m³, 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection:



Tightly sealed goggles

	<b>SECTION 9:</b>	<b>Physical</b>	and cl	hemical	properties
--	-------------------	-----------------	--------	---------	------------

· 9.1 Information or	hasic physical and	chemical	nronerties
· 7.1 III/OHHUUUUII OH	ı vusic viivsicui unu	Chemicai	DIODEILLES

· General Information

· Appearance:

· pH-value:

Form: Aerosol Colour: Colourless Solvent-like · Odour: Not determined. · Odour threshold: Not determined.

· Change in condition

Undetermined. Melting point/Melting range:

Boiling point/Boiling range: Not applicable, as aerosol.

<0 °C (<32 °F) · Flash point:

Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

240 °C (464 °F) · Ignition temperature:

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour · Danger of explosion:

mixtures are possible.

· Explosion limits:

1.2 Vol % Lower: 26.2 Vol % Upper:

· Vapour pressure at  $20 \, {}^{\bullet}C$  (68  ${}^{\bullet}F$ ): 4000 hPa (3000 mm Hg)

· Density at 20 °C (68 °F):  $0.725 \text{ g/cm}^3 (6.05 \text{ lbs/gal})$ 

· Relative density Not determined. · Vapour density Not determined.

(Contd. on page 6)

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

	(Co	ntd. of page :
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octano	l/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	93.9 %	
· EU-VOC:	682.1 g/l	
· EU-VOC in %:	93.92 %	
· Water:	0.2 %	
· Solids content:	5.9 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11:	Toxicolo:	gical in	formation

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

		ant for classification:
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50/4 h	39 mg/m3 (rat)
115-10-6 d	limethyl eth	er
Inhalative	LC50/4 h	308 mg/m3 (rat)
123-86-4	ı-butyl acete	nte The state of t
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/m3 (rat)
108-65-62	2-methoxy-1	-methylethyl acetate
Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/m3 (rat)
106-97-8 l	outane	
Inhalative	LC50/4 h	658000 mg/m3 (rat)
71-36-3 bi	itan-1-ol	•
Oral	LD50	2292 mg/kg (rat)

(Contd. on page 7)

 Printing date 16.12.2016
 Version number 12
 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

)
1

Dermal LD50 3430 mg/kg (rabbit) Inhalative LC50/4 h 17.76 mg/m3 (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

12.1 10.0000		
· Aquatic toxicity:	· Aquatic toxicity:	
67-64-1 acetone		
EC50 / 48 h	8800 mg/l (daphnia magna)	
LC50 / 48 h	2262 mg/l (daphnia magna)	
LC50 / 96 h (static)	5540 mg/l (fish)	
115-10-6 dimethyl e	ther	
EC50 / 48 h	>4000 mg/l (daphnia magna)	
123-86-4 n-butyl acetate		
EC50 / 48 h	44 mg/l (daphnia magna)	
EC50 / 96 h	320 mg/l (algae)	
LC50 / 24 h	205 mg/l (daphnia magna)	
LC50 / 96 h	18 mg/l (Pimephales promelas)	
108-65-6 2-methoxy-1-methylethyl acetate		
EC50 408 mg/l (daphnia magna)		
71-36-3 butan-1-ol		
EC50 / 48 h	1328 mg/l (daphnia magna)	
EC50 / 72 h	8500 mg/l (algae)	
LC50/96 h	1376 mg/l (Pimephales promelas)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

Printing date 16.12.2016 Version number 12 Revision: 15.12.2016

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

(Contd. of page 7)

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue
   08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances
   15 01 04 metallic packaging
- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	<ul><li>2 5F Gases.</li><li>2.1</li></ul>
· Class · Label	2. <i>I</i> 2. <i>I</i>
· Label · 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases.  F-D,S-U  SW1 Protected from sources of heat.  SW22 For AEROSOLS with a maximum capacity of 1 lit  Category A. For AEROSOLS with a capacity above 1 lit  Category B. For WASTE AEROSOLS: Category C, Clea  of living quarters.  SG69 For AEROSOLS with a maximum capacity of 1 lit  Segregation as for class 9. Stow "separated from" class  except for division 1.4. For AEROSOLS with a capacity  above 1 litre: Segregation as for the appropriate

(Contd. on page 9)

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

	(Contd. of page
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: QHSE Department
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)

Trade name: UDO CLEAR LACQUER BLANCO 500 ML

(Contd. of page 9)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

– Gl