

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML
- **Article number:** IND(xxxx)
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**  
PROC7 Industrial spraying  
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Preparation
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
PROXL  
1 Mantle Close  
Bingham Road, Sittingbourne  
ME10 3BW Kent  
United Kingdom  
Tel: +44 (0)1634 823900  
Fax: +44 (0)1634 823909  
Email: sales@capellasolutionsgroup.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
Tel: +44(0) 1634 823900 (08.00 / 17.00)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

#### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02

- **Signal word** Danger
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

**Trade name: PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 1)

· **Precautionary statements**

- P101 *If medical advice is needed, have product container or label at hand.*  
 P102 *Keep out of reach of children.*  
 P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*  
 P211 *Do not spray on an open flame or other ignition source.*  
 P251 *Do not pierce or burn, even after use.*  
 P260 *Do not breathe spray.*  
 P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*  
 P501 *Dispose of contents / container in accordance with regional regulations.*

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**


- **PBT:** Not applicable.  
 · **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6	dimethyl ether	 <b>Flam. Gas 1, H220</b> <b>Press. Gas (Comp.), H280</b>	75-≤100%
EINECS: 204-065-8			
Index number: 603-019-00-8			
Reg.nr.: 01-2119472128-37			

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.  
 · **After skin contact:** Generally the product does not irritate the skin.  
 · **After eye contact:** Rinse opened eye for several minutes under running water.  
 · **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.  
 · **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.  
 · **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

*During heating or in case of fire poisonous gases are produced.*

· **5.3 Advice for firefighters -**

- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

*Mount respiratory protective device.*

*Wear protective equipment. Keep unprotected persons away.*

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

*Dispose contaminated material as waste according to item 13.*

*Ensure adequate ventilation.*

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

**Trade name: PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 2)

- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
No special measures required.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 766 mg/m <sup>3</sup> , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

Trade name: **PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 3)

· **Eye protection:** Not required.

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· **Form:** Gaseous  
· **Colour:** Colourless

· **Odour:** Mild

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

##### · Change in condition

· **Melting point/freezing point:** -141.5 °C (-222.7 °F)

· **Initial boiling point and boiling range:** Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Explosive properties:** Not determined.

##### · Explosion limits:

· **Lower:** 3.3 Vol %

· **Upper:** 26.2 Vol %

· **Vapour pressure at 20 °C (68 °F):** 4000 hPa (3000.2 mm Hg)

· **Density at 20 °C (68 °F):** 0.66 g/cm<sup>3</sup> (5.51 lbs/gal)

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not applicable.

##### · Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

##### · Viscosity:

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

##### · Solvent content:

· **Organic solvents:** 94.0 %

· **VOC (EC):** ---

621.3 g/l

· **VOC-EU%:** 94.00 %

· **Solids content:** 0.0 %

· **9.2 Other information:** No further relevant information available.

### SECTION 10: Stability and reactivity

· **10.1 Reactivity:** No further relevant information available.

#### · 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions:** No dangerous reactions known.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

Trade name: **PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 4)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**115-10-6 dimethyl ether**

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

20 01 13*	solvents
15 01 04	metallic packaging

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60



Revision: 23.04.2019

Trade name: **PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 5)

- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b> · <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b> · <b>ADR</b> · <b>IMDG, IATA</b>	1950 AEROSOLS AEROSOLS
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b>	
· <b>Class</b> · <b>Label</b>	2 5F Gases. 2.1
· <b>IMDG, IATA</b>	
· <b>Class</b> · <b>Label</b>	2 Gases. 2.1
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	not regulated
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. 23 F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.08.2019

Version number 60

Revision: 23.04.2019

Trade name: **PROXL INDUSTRIAL ACRYLIC TOPCOAT - 500ML**

(Contd. of page 6)

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a** FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Contact:** QHSE Department

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas