

**UPOL BODYFILLER RANGE** 

Page: 1

Compilation date: 12/12/2007

**Revision date:** 06/03/2012

Revision No: 4

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: UPOL BODYFILLER RANGE

Product code: VARIOUS

Synonyms: P38, P40, FIBRAL, QUICKSAND, DOLPHIN, EASY, MONARCH, EASYLITE,

EXTRA, EXTRA GOLD, FANTASTIC, HOTSHOT, GALVX, SMC, SUPERB, TOPSTOP, FLYWEIGHT, TOPSTOP GOLD, UPOL B, UPOL C, BUMPERFILL,

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: POLYESTER REPAIR PASTE CONTAINING STYRENE

#### 1.3. Details of the supplier of the safety data sheet

Company name: U-POL Limited

**Denington Industrial Estate** 

Denington Road Wellingborough

Nothants NN8 2QH

United Kingdom

Tel: +44-(0)-1933 230300

Fax: +44-(0)-1933 425797

Email: technical@u-pol.com

## 1.4. Emergency telephone number

Emergency tel: +44-(0)-1933 230310

### Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20; Xi: R36/38

Most important adverse effects: Harmful by inhalation. Irritating to eyes and skin.

#### 2.2. Label elements

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

**UPOL BODYFILLER RANGE** 

Page: 2

Safety phrases: S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

#### 2.3. Other hazards

Other hazards: Flammable. Harmful by inhalation. Irritating to eyes. Irritating to skin.

PBT: This substance is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

#### STYRENE.

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-851-5	100-42-5	-: R10; Xn: R20; Xi: R36/38; Xn:	-	10-30%
		R48/20		

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

**UPOL BODYFILLER RANGE** 

**Page:** 3

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

# Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	maa 001	250 ppm	1 mg/m3	-

## **Hazardous ingredients:**

### STYRENE.

## Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	430 mg/m3	1080 mg/m3	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protective device with particle filter.

Hand protection: Nitrile gloves.

**UPOL BODYFILLER RANGE** 

Page: 4

**Eye protection:** Safety glasses with side-shields.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Paste

**Odour:** Aromatic

Evaporation rate: Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Kinematic viscosity: 500,000 CP

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Flammability limits %: lower: 1.1 upper: 6.1

Flash point°C: 32 Autoflammability°C: 490

Relative density: 1.50 VOC g/l: 300

#### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

#### 10.5. Incompatible materials

Materials to avoid: Oxidising agents.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

**UPOL BODYFILLER RANGE** 

Page: 5

#### Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH	Hazardous: calculated
Irritation	OPT DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: Not applicable.

### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

## 12.4. Mobility in soil

Mobility: Insoluble in water. Heavier than water.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

### 12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

### Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Deposit into or on to land (e.g. landfill, etc.)

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

## 14.1. UN number

UN number: UN3269

**UPOL BODYFILLER RANGE** 

Page: 6

## 14.2. UN proper shipping name

Shipping name: POLYESTER RESIN KIT

### 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

## **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate

personal protective equipment should always be used.

Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local

stockist or via the U-POL website at WWW.U-POL.COM.

U-POL disclaim any liability where the user does not wear the recommended personal

protective equipment.

Phrases used in s.2 and 3: R10: Flammable.

R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

## **UPOL BODYFILLER RANGE**

Page: 7

and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.