

Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: TREMCO SF115

· MSDS code: W-T-SF115

• 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.

· Application of the substance / the mixture Adhesives

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410 msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

#### · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS07 GHS08 GHS09

· Signal word Danger

(Contd. on page 2)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

Trade name: TREMCO SF115

(Contd. of page 1)

#### Contains:

toluene

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

acetone

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Do not breathe vapours. P260

Wear protective gloves/protective clothing/eye protection/face protection. P280

P273 Avoid release to the environment.

P202 Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a doctor. P301+P310

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

P331 Do NOT induce vomiting.

#### · Supplemental information:

EUH208 Contains Rosin. May produce an allergic reaction.

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,	20- <30%
Reg.nr.: 01-2119475515-33-xxxx	<5% n-hexane	
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
	(Cor	itd. on page 3)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

		(Cor	ntd. of page 2)
	CAS: 108-88-3	toluene	20- <30%
	EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3,	
	Reg.nr.: 01-2119471310-51-xxxx	Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3,   H336	
		F1000	
	CAS: 78-93-3	butanone	10- <20%
	EINECS: 201-159-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3,	
	Reg.nr.: 01-2119457290-43-xxxx	H336	
	CAS: 67-64-1	acetone	10- <20%
	EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3,	
	Reg.nr.: 01-2219471330-49-xxxx	H336	
	CAS: 8050-09-7	Rosin	0.1- <1%
	EINECS: 232-475-7	Skin Sens. 1, H317	
	Reg.nr.: 01-2119480418-32-xxxx		
	CAS: 1314-13-2	zinc oxide	0.1- <1%
	EINECS: 215-222-5	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Reg.nr.: 01-2119463881-32-xxxx		
	CAS: 110-54-3	n-hexane	0.1- <1%
	EINECS: 203-777-6	Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373;	
	Reg.nr.: 01-2119480412-44-xxxx	Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit.	
		2, H315; STOT SE 3, H336	
. –		I .	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

#### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

#### · After inhalation:

Supply fresh air.

Seek immediate medical advice.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- $\cdot$  4.2 Most important symptoms and effects, both acute and delayed

Harmful: may cause lung damage if swallowed.

**Dizziness** 

Vapours have narcotic effect.

Breathing difficulty

Disorientation

Allergic reactions

Irritating to eyes and skin.

· Information for doctor: No further relevant information available.

(Contd. on page 4)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 3)

- · Hazards No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed.

  No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Keep people at a distance and stay on the windward side.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Information about fire - and explosion protection:

Highly flammable.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 5)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

· Information about storage in one common storage facility:

Store away from oxidising agents.

Protect from heat and direct sunlight.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

<ul> <li>Ingredients with limit values that require monitoring at the workplace:</li> </ul>
---

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

TWA Long-term value: 1200 mg/m<sup>3</sup>

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm

Long-term value: 191 mg/m³, 50 ppm

Sk

78-93-3 butanone

WEL | Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

67-64-1 acetone

WEL | Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

8050-09-7 Rosin

WEL | Short-term value: 0.15 mg/m<sup>3</sup>

Long-term value: 0.05 mg/m<sup>3</sup>

Sen

110-54-3 n-hexane

WEL Long-term value: 72 mg/m³, 20 ppm

## · Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

#### Additional information:

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

(Contd. on page 6)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 5)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Do not eat, drink, smoke or sniff while working.

Respiratory protection:

Use only in well-ventilated areas.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Filter AX

Take note of emission threshold.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Viscous
Colour: Light brown
Odour: Solvent-like

· Initial boiling point and boiling range: 56 °C

(Contd. on page 7)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

	(Contd. of page 6)
· Flash point:	<-18 °C
· Ignition temperature:	>200 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	0.9 Vol % 13.0 Vol %
· Density at 20 °C:	0.86 g/cm³
· Solubility in / Miscibility with water:	Insoluble.
· Viscosity: Dynamic at 20 °C:	4500 mPas
Solvent content:     VOC (EC)     9.2 Other information	665 g/l No further relevant information available.

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Oral	LD50	> 2000 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rabbit)	
108-88-3 1	108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/L (mouse)	
1314-13-2 zinc oxide			
Oral	LD50	> 5000 mg/kg (rat)	
		(Contd. on page 8)	

on page



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 7)

· Primary irritant effect:

· Skin corrosion/irritation

Strong degreasing effect.

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

Sensitising effect by skin contact is possible by prolonged exposure.

· Additional toxicological information:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

CAS 108-88-3; Repr. 2 (CLP)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

	•		4	
•	Aα	uatic	tox	ICITV:

## Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50/48 h 36 mg/L (fish)

EC50/72 h | 30 mg/L (pseudokirchneriella subcapit.)

#### 1314-13-2 zinc oxide

LC50/96 h 1.1 mg/L (fish)

EC50/48 h >1000 mg/L (daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

### · Ecotoxical effects:

### 1314-13-2 zinc oxide

IC50/72 h 0.1-1 mg/L (algae)

- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 9)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Waste disposal key: UK (WM3): HP3 HP4 HP5 HP10 HP14

#### · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

## **SECTION 14: Transport information**

· 14.1 UN-Number · ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name	
· ADR	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS
· IMDG	ADHESIVES (Naphtha (petroleum), hydrotreated light, zinc oxide), MARINE POLLUTANT
· IATA	ADHESIVES "

- · 14.3 Transport hazard class(es)
- · ADR





ClassLabel3 (F1) Flammable liquids.3

· IMDG





· Class 3 Flammable liquids.

(Contd. on page 10)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

<b>Trade</b>	name:	<b>TREMCO</b>	SF115
--------------	-------	---------------	-------

	(Contd. of page
· Label	3
· IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardou substances: zinc oxide
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	- 
· EMS Number: · Stowage Category	F-E,S-D B
· 14.7 Transport in bulk according to Anno	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 100  ml
Transport category	3
· Tunnel restriction code	E 
· IMDG · Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
, ,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III ENVIRONMENTALLY HAZARDOUS

# **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).
  - "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). (Contd. on page 11)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

Trade name: TREMCO SF115

(Contd. of page 10)

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 5, 48
- National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Other regulations, limitations and prohibitive regulations

"REACH" Regulation (EC) No 1907/2006; ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. on page 12)



Printing date 04.04.2017 Version number 4 Revision: 04.04.2017

**Trade name: TREMCO SF115** 

(Contd. of page 11)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· \* Data compared to the previous version altered.

-GB-