

Page 1 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Tire fitting paste black 5 kg Art.: 337832

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Assembly material

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00 info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).



_Œ

Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

<u> </u>	
Diethylene glycol	
Registration number (REACH)	01-2119457857-21-XXXX
Index	603-140-00-6
EINECS, ELINCS, NLP	203-872-2
CAS	111-46-6
content %	1-5
Classification according to Regulation (EC)	Acute Tox. 4, H302
1272/2008 (CLP)	STOT RE 2, H373 (kidneys) (oral)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion



Page 3 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

with long-term contact:

Irritation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.



_GB

Page 4 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Or:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store cool.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diethylene glycol		Content %:1-5
WEL-TWA: 23 ppm (101	mg/m3) WEL-STEL:		
Monitoring procedures:	 Draeger - Alcohol 100/a (CH 29 701) 		
BMGV:	Other informatio	n:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value,



Page 5 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Diethylene glycol Area of application	Exposure route /	Effect on	Descrip	Value	Unit	Note
Area or application	Environmental	health	tor	value	Oilit	NOTE
	compartment	Health	toi			
	Environment -		PNEC	10	mg/l	
	freshwater		FINEC	10	1119/1	
	Environment - marine		PNEC	1	mg/l	
	Environment -		PNEC	20,9		
			PINEC	20,9	mg/kg	
	sediment, freshwater Environment - soil		PNEC	1,53	ma /l/a	
					mg/kg	
	Environment -		PNEC	199,5	mg/l	
	sewage treatment					
	plant					
	Environment -		PNEC	10	mg/l	
	water, sporadic					
	(intermittent) release					
	Environment -		PNEC	2,09	mg/kg	
	sediment, marine				dry	
					weight	
Consumer	Human - dermal	Long term,	DNEL	21	mg/kg	
		systemic effects				
Consumer	Human - inhalation	Long term,	DNEL	12	mg/m3	
		systemic effects				
Workers / employees	Human - dermal	Long term,	DNEL	43	mg/kg	
. 3		systemic effects				
Workers / employees	Human - inhalation	Long term,	DNEL	44	mg/m3	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		systemic effects] 3.	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.



Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Normally not necessary.

Protective hand cream recommended.

With long-term contact: Rubber gloves (EN 374).

Protective plastic gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

>=0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Paste, Liquid

Colour: According to specification

Odour: Mild

Odour threshold: Not determined pH-value: ~8 (20°C, Emulsion)



Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Melting point/freezing point: ~50 °C

Initial boiling point and boiling range: n.a.

Flash point: ~240 °C (DIN 51376 (Cleveland, open cup))

Evaporation rate: Not determined

Flammability (solid, gas):

Lower explosive limit:

upper explosive limit:

n.a.

Vapour pressure:

Vapour density (air = 1):

Density:

Not determined

Not determined

1,06 g/cm3 (20°C)

Bulk density: n.a.

Solubility(ies): Not determined

Water solubility: Mixable

Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: ~400 °C (DIN 51794, Ignition temperature)

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

No dangerous reactions are known.

None known

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification)

Tire fitting paste black 5 kg

Art.: 337832



Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral	nt ATE	>2000	mg/kg			calculated
route:	'	- 2000	g,g			value
Acute toxicity, by						n.d.a.
dermal route:						111211
Acute toxicity, by						n.d.a.
inhalation:						
Skin						n.d.a.
corrosion/irritation:						
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						According
						to current
						knowledge
						that mixture
						does not
						endanger
						man under
						normal
						conditions
						of
						application.

Diethylene glycol							
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	13300	mg/kg	Rabbit		Analogous conclusion	
Acute toxicity, by inhalation:	LC50	>4,6	mg/l/4 h			Not relevant., expert judgement	
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Not irritant	
Serious eye damage/irritation:				Rabbit		Not irritant	



(GB)

Page 9 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Respiratory or skin sensitisation:	Guinea pig		No (skin contact)
Germ cell mutagenicity:	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:	Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:	Mouse		Negative
Reproductive toxicity:	Rabbit	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Symptoms:			acidosis, breathing difficulties, unconscious ness, diarrhoea, coughing, cramps, fatigue, mucous membrane irritation, dizziness, nausea and vomiting., trembling

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Tire fitting paste black 5 kg Art.: 337832							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							Readily
and degradability:							biodegradabl
							е



Page 10 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

12.3.				n.d.a.
Bioaccumulative potential:				
12.4. Mobility in soil:				n.d.a.
12.5. Results of PBT and vPvB assessment				n.d.a.
12.6. Other adverse effects:				n.d.a.
Other information:	AOX			According to the recipe, contains no AOX.
Other information:	DOC			DOC- elimination degree(com plexing organic substance) > = 80%/28d: n.a.

Diethylene glycol	Diethylene glycol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to	LC50	96h	75200	mg/l	Pimephales			
fish:					promelas			
12.1. Toxicity to	LC50	96h	>320	mg/l	Gambusia			
fish:			00	1	affinis			
12.1. Toxicity to	EC50	24h	>100	mg/l	Daphnia	DIN 38412		
daphnia:			00	1	magna	T.11		
12.1. Toxicity to	NOEC/NOE	72h	100	mg/l	Scenedesmus		References	
algae:	L				quadricauda			
12.2. Persistence	DOC	28d	90-	%		OECD 301 A		
and degradability:			100			(Ready		
						Biodegradabili		
						ty - DOC Die-		
						Away Test)		
12.3.	BCF	3d	100					
Bioaccumulative								
potential:								
Toxicity to	EC20	30min	1995	mg/l	Pseudomonas	ISO 8192	References	
bacteria:					putida			

SECTION 13: Disposal considerations

13.1 Waste treatment methods
For the substance / mixture / residual amounts



Page 11 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

LQ (ADR 2015):

n.a.

n.a.

Factor:

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information



(GB)

Page 12 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

n.a.

Revised sections:

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure if swallowed. H302 Harmful if swallowed.

Acute Tox. — Acute toxicity - oral

STOT RE — Specific target organ toxicity - repeated exposure

Albert Berner Deutschland GmbH

Bernerstrasse 4 D - 74653 Künzelsau Tel +49 79 40 12 10 Fax +49 79 40 12 13 00

info@berner.de www.berner.de

Berner Gesellschaft m.b.H.

Industriezeile 36 A - 5280 Braunau / Inn Tel +43 77 22 800 508 Fax +43 77 22 800 184 berner@berner.co.at

www.berner.co.at

Berner Belgien NV/SA Bernerstraat 1

B - 3620 Lanaken

Tel +31 45 533 93 133(8.00h-16.00h)

Tol. 0011)

Tel +31 6 290 27 464 (16.00h-

8.00h)

Fax +31 455 33 92 43

info@berner.be www.berner.be

P.I. "La Rosa VI"

Montagetechnik Berner AG

Kägenstraße 8

CH - 4153 Reinach / Bl. 1 Tel +41 61 71 59 222 Fax +41 61 71 59 333 berner-ag@berner-ag.ch www.berner-ag.ch Berner A/S Stenholm 2

www.berner.dk

DK - 9400 Nørresundby Tel +45 99 36 15 00 Fax +45 98 19 24 14 info@berner.dk

C/Albert Berner, 2 E - 18330 Chauchina-Granada-España

Berner Montaje y Fijación, S.L.

Tel +34 90 21 03 504 Fax +34 90 21 13 190 berner-spain@berner.es

www.berner.es



Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Berner Kft.
Táblás u. 34
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS Holmaveien 25 N - 1339 Vøyenenga Tel +47 66 76 55 80 Fax +47 66 76 55 81 info@berner.no www.berner.no Berner Succ. Luxembourg 105, Rue des Bruyères L - 1274 Howald Tel +31 45 533 93 133 (8.00h-16.00h) Tel +31 6 290 27 464 (16.00h-8.00h) Fax +31 455 33 92 43 info@berner.lu www.berner.lu

Berner spol. s r.o. Jinonická 80 CZ - 158 00 Praha 5 Tel +420 225 390 666 Fax +420 225 390 660 berner@berner.cz www.berner.cz Berner,S.A.
Av. Amália Rodrigues,3510
Manique de Baixo
P - 2785-738 Săo Domingos de Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69
marketing.pt@berner.pt
www.berner.pt

Berner Polska Sp. z o.o. UI. Puszkarska 7J 30-644 Kraków Tel +48 12 297 62 40 Fax +48 12 297 62 02 office@berner.pl www.berner.pl

Albert Berner UAB Kalvarijø 29B, LT09313, Vilnius, Lithuania Tel +370-52104355 Fax +370-52350020 info@berner.lt

Berner SK Berner s r.o. Jesenského 1 SK - 962 12 Detva Tel (+421) 45 5410 245 Fax (+421) 45 5410 255 berner@berner.sk www.berner.sk Albert Berner Montageteknik AB Elektravägen 53 S - 126 30 Hägersten Tel +46 85 78 77 800 Fax +46 85 78 77 805 info@berner.se www.berner.se

Berner Pultti Oy Volttikatu 6 FI - 70700 Kuopio Tel +358-207-590 220 Fax +358-207-590 221 kuopio@berner-pultti.com www.berner-pultti.com

Mitras d.o.o Brdnikova ulica 34e SL-1000 Ljubljana Tel +386-1-256-62-46 Fax +386-1-256-62-45 mitras@siol.com BERNER d.o.o CPM Savěca Śanci Trgovaćka 2 HR - 10000 Zagreb Tel +38512 499 470 Fax +38512 499 480 e-mail: safetydata-hr@berner.co.at

Berner Endüstriyel Ürünler Sanayi ve Ticaret A.Ţ. Ferhatpaṭa Mah. G 7 Sok. 31/2 TR - 34858 Kartal-Samandýra / ÝSTANBUL Tel +90 (0) 216-4713077 Fax +90 (0) 216-4719625 info@berner.com.tr Berner S.p.A. Via dell 'Elettronica 15 I - 37139 Verona Tel +39 04 58 67 01 11 Fax +39 04 58 67 01 34 info@berner.it www.berner.it

Albert Berner srl Str. Vrancei Nr. 51 - 55 RO - 310315 Arad Tel +40 257 212291 Fax +40 257 250460 office@berner-romania.ro www.berner-romania.ro



Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

Berner Produkten b.v. Vogelzankweg 175

NL - 6374 AC Landgraaf

+31 45 53 39 133 (8.00h-16.00h) +31 6 290 27 464 (16.00h-8.00h)

info@berner.nl www.berner.nl Berner s.a.r.l. ZI Les Manteaux

F - 89331 Saint-Julien-du-Sault Cedex

Tel +33 38 69 94 400 Fax +33 38 69 94 444 contact@berner.fr www.berner.fr Albert Berner SIA

Liliju 20, Marupe, Mārupes novads, LV-2167, Latvija

Tel +37167840007 Fax +371678440008 info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon



(GB)

Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for

Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level



Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.11.2016 / 0001

Replacing version dated / version: 03.11.2016 / 0001

Valid from: 03.11.2016 PDF print date: 03.11.2016 Tire fitting paste black 5 kg

Art.: 337832

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.