according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE

Revision date:30/12/2022Version:1.2Replaces version:1.1Language:en-GBDate of print:7/6/2023

Page:

1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

This safety data sheet pertains to the following products: 367074 = HIGH PERFORMANCE LUBRICANT PTFE PREMIUM 408461 = HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricating agent. Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company name:	Berner Produkten b.v.
Street/POB-No.:	Vogelzankweg 175
Postal Code, city:	6374 AC Landgraaf
	Netherlands
WWW:	www.berner.nl
E-mail:	info@berner.nl
Telephone:	+31 45 53 39 133

Department responsible for information:

E-mail: Productsafety.Chemicals@berner-group.com

1.4 Emergency telephone number

Poisons information service: National Poisons Information Service (Birmingham Unit): 844 892 0111 Transport: CONSULTANK Lutz Harder GmbH (Contract Qualisys/Berner) Telephone: +49 (178) 4337434 (from USA: 01149 178 4337434)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:	Danger	
Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H412	Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/12/2022 Version: 1.2 Replaces version: 1.1 Language: Date of print: en-GB 7/6/2023

Page:

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

2 of 9

Precautionary statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P273	Avoid release to the environment.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

CAS No.	Designation	PBT/vPvB	ED Human	ED Environment
1330-78-5	Tris(methylphenyl) phosphate		List III	

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Identifiers	Designation Classification	Content
EC No. 215-548-8 CAS 1330-78-5	Tris(methylphenyl) phosphate Repr. 2; H361fd. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.	< 2.5 %
REACH 01-2119474691-32-xxxx EC No. 203-448-7 CAS 106-97-8	n-Butane, <0,1% Butadiene Flam. Gas 1; H220. Press. Gas (Comp.); H280.	25 - 50 %
REACH 01-2119486944-21-xxxx EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	5 - 10 %
REACH 01-2119485395-27-xxxx EC No. 200-857-2 CAS 75-28-5	i-Butane, <0,1% Butadiene Flam. Gas 1; H220. Press. Gas (Comp.); H280.	1 - 2.5 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand.
In case of inhalation:	Move victim to fresh air. In the event of discomfort seek medical treatment.
Following skin contact:	Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.
After swallowing:	Do not induce vomiting. Rinse mouth and seek medical attention immediately.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 en-GB Language Date of print: 7/6/2023

Page:

3 of 9

4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide, Water spray jet, Extinguishing powder, alcohol resistant foam.

Extinguishing media which must not be used for safety reasons Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. May form dangerous gases and vapours in case of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. Additional information Hazchem-Code: -

> Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe spray. Avoid contact with the substance. In case of leakage, eliminate all ignition sources. Provide adequate ventilation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away. Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

6.4 Reference to other sections

Refer additionally to section 8 and 13.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 Language: Date of print: en-GB 7/6/2023

Page:

4 of 9

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling:	Provide adequate ventilation, and local exhaust as needed. Do not breathe spray. Avoid		
	inhalation and contact with skin and eyes.		
	Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Take off		
	contaminated clothing and wash it before reuse.		
	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.		
	When handling large quantities, supply emergency spray.		
Precautions against fire and	explosion:		
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No		
	smoking. Take precautionary measures against static discharge. Do not pierce or burn, even		

n after use. Do not spray on an open flame or other ignition source.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storeroom	is and containers:
	Keep container tightly closed and in a well-ventilated place.
	Keep container dry. Keep only in the original container.
	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	Store containers in upright position.
Hints on joint storage:	Keep away from food, drink and animal feedingstuffs.
7 2 Spacific and	

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS No.	Designation	Туре	Limit value
106-97-8	n-Butane, <0,1% Butadiene	Great Britain: WEL-STEL	1810 mg/m³; 750 ppm
		Great Britain: WEL-TWA	1450 mg/m³; 600 ppm

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection:	In case of inadequate ventilation wear respiratory protection. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection:	Protective gloves according to EN 374. Glove material: Nitrile rubber - Layer thickness: > 0.68 mm. penetration time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to BS EN ISO 16321-1:2022.
Body protection:	Flame retardant, antistatic and chemical resistant protective clothing.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 Language: en-GB 7/6/2023 Date of print:

Page:

5 of 9

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Do not breathe spray. Do not get in eyes, on skin, or on clothing.

When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace.

Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Odour:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol Colour: brown characteristic
Odour threshold:	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	Not applicable
Flash point/flash point range:	-71 °C
Evaporation rate:	No data available
Flammability:	Extremely flammable aerosol.
Explosion limits:	No data available
Vapour pressure:	No data available
Vapour density:	No data available
Density:	at 20 °C: 0.92 g/cm³
Water solubility:	Slightly miscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	Not self-igniting
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

9.2 Other information

Additional information:

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 Language: en-GB Date of print: 7/6/2023

Page:

6 of 9

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed. Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects:	The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
	Acute toxicity (oral): Based on available data, the classification criteria are not met.
	Acute toxicity (dermal): Based on available data, the classification criteria are not met.
	Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
	Skin corrosion/irritation: Based on available data, the classification criteria are not met.
	Serious eye damage/irritation: Based on available data, the classification criteria are not met.
	Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.
	Skin sensitisation: Based on available data, the classification criteria are not met.
	Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.
	Carcinogenicity: Based on available data, the classification criteria are not met.
	Reproductive toxicity: Based on available data, the classification criteria are not met.
	Effects on or via lactation: Lack of data.
	Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.
	Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.
	Aspiration hazard: Based on available data, the classification criteria are not met.
Other information:	Information about Tris(methylphenyl) phosphate: LD50 Rat, oral: > 3,700 mg/kg LD50 Rabbit, dermal: 10,000 mg/kg

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 Language: en-GB Date of print: 7/6/2023

Page:

7 of 9

12.2 Persistence and degradability

Further details:

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information:

Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Ρ	rodu	ct
---	------	----

Waste key number:	 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances / Aerosol * = Evidence for disposal must be provided. 	
Recommendation:	Do not pierce or burn, even after use.	
	Special waste. Dispose of waste according to applicable legislation.	
	Do not dispose of with household waste.	
Package		
Waste key number:	15 01 04 = metallic packaging	
Recommendation:	Dispose of waste according to applicable legislation. Empty carefully and completely, if possible. Handle contaminated packages in the same way as the substance itself. Handle empty containers with care. Incineration may cause explosion.	

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR: UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG:	UN 1950, AEROSOLS
IATA-DGR:	UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID:	Class 2, Code: 5F
IMDG:	Class 2.1, Subrisk -
IATA-DGR:	Class 2.1

14.4 Packing group

ADR/RID, IATA-DGR:	not applicable
IMDG:	-



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces version: 1.1 Language: Date of print: en-GB 7/6/2023

Page:

8 of 9

14.5 Environmental hazards

Marine pollutant:

14.6 Special precautions for user

no

Land transport (ADR/RID)

Warning board: Hazard label: Special Provisions: Limited quantities: EQ: Package - Instructions: Package - Special Provisions: Special provisions for packing together: Tunnel restriction code:	RID: Kemmler-number 23, UN number UN 1950 2.1 190 327 344 625 1 L E0 P207 LP200 PP87 RR6 L2 MP9 D
Sea transport (IMDG)	
EmS:	F-D, S-U
Special Provisions:	63 190 277 327 344 381 959
Limited quantities:	1000 mL
Excepted quantities:	E0
Package - Instructions:	P207, LP200
Package - Provisions:	PP87, L2
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	SW1 SW22
Segregation:	SG69
Properties and observations:	-
Segregation group:	none
Air transport (IATA)	
Hazard label:	Flamm. gas
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions:	A145 A167 A802
Emergency Response Guide-Code (ERG):	10L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code:

No data available

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

ERNER HIGH PERFORMANCE LUBRICANT PTFE PREMIUM

Revision date: 30/12/2022 Version: 1.2 Replaces vers 1.1 Language: en-GB Date of print: 7/6/2023

Page

9 of 9

National regulations - EC member states

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg

Use restriction according to REACH annex XVII, no.: 3, 40, 75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P3a.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3: H220 = Extremely flammable gas. H222 = Extremely flammable aerosol. H229 = Pressurised container: May burst if heated. H280 = Contains gas under pressure; may explode if heated. H361fd = Suspected of damaging fertility. Suspected of damaging the unborn child. H400 = Very toxic to aquatic life. H410 = Very toxic to aquatic life with long lasting effects. H412 = Harmful to aquatic life with long lasting effects. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways Abbreviations and acronyms: ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road Aerosol: Aerosol Aquatic Acute: Hazardous to the aquatic environment - acute Aquatic Chronic: Hazardous to the aquatic environment - chronic AS/NZS: Australian Standards/New Zealand Standards CAS: Chemical Abstracts Service CFR: Code of Federal Regulations CLP: Classification, Labelling and Packaging DMEL: Derived minimal effect level DNEL: Derived no-effect level EC: European Community EN: European Standard EQ: Excepted quantities EU: European Union Flam. Gas: Flammable gases IATA: International Air Transport Association IATA-DGR: International Air Transport Association - Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IMDG Code: International Maritime Dangerous Goods Code LD50: Lethal dose 50% MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic PNEC: Predicted no-effect concentration Press. Gas: Gases under pressure REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Repr.: Reproductive toxicity RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail TRGS: Technical Rules for Hazardous Substances UN: United Nations vPvB: Very persistent and very bioaccumulative Reason of change General revision

Date of first version:

16/3/2021

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations