

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

 Revision date:
 6/6/2023

 Version:
 1.4

 Replaces version:
 1.3

 Language:
 en-GB

 Date of print:
 7/6/2023

 Page:
 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

Electronic spray

This safety data sheet pertains to the following products: 22509 = Electronic spray 409469 = Electronic spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: auxiliaries. Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company name:	Berner Produkten b.v.
Street/POB-No.:	Vogelzankweg 175

 Postal Code, city:
 6374 AC Landgraaf

 Netherlands

 WWW:
 www.berner.nl

 E-mail:
 info@berner.nl

 Telephone:
 +31 45 53 39 133

Department responsible for information:

E-mail: Productsafety.Chemicals@berner-group.com

1.4 Emergency telephone number

Poisons information service: National Poisons Information Service (Birmingham Unit): 844 892 0111 Transport: CONSULTANK Lutz Harder GmbH (Contract Qualisys/Berner) Telephone: +49 (178) 4337434 (from USA: 01149 178 4337434)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229Extremely flammable aerosol. Pressurised container: May burst if heated.Skin Irrit. 2; H315Causes skin irritation.STOT SE 3; H336May cause drowsiness or dizziness.Asp. Tox. 1; H304May be fatal if swallowed and enters airways.Aquatic Chronic 2; H411Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:	Danger	
Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:6/6/2023Version:1.4Replaces version:1.3Language:en-GBDate of print:7/6/2023Page:2 of 11

Precautionary statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	P211	Do not spray on an open flame or other ignition source.	
	P251	Do not pierce or burn, even after use.	
	P261	Avoid breathing vapours/spray.	
	P273	Avoid release to the environment.	
	P312	Call a POISON CENTER/doctor if you feel unwell.	
	P391	Collect spillage.	
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
Special labelling			
	EUH208	Contains (R)-p-Mentha-1,8-diene. May produce an allergic reaction.	
Text for labelling:	Contains:		
	Pentane		
Hydrocarbons, C6, isoalkanes, < 5% n-hexane		s, C6, isoalkanes, < 5% n-hexane	

White mineral oil (petroleum)

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect. The product is skin resorptive. Special danger of slipping by leaking/spilling product.. Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Blend of active ingredients with propellant.

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119459286-30-xxxx EC No. 203-692-4 CAS 109-66-0	Pentane Flam. Liq. 2; H225. Skin Irrit. 2; H315. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).	25 - 50 %
REACH 01-2119473851-33-xxxx list no. 920-750-0 CAS 64742-49-0	Hydrocarbons, C6, isoalkanes, < 5% n-hexane Flam. Liq. 2; H225. Skin Irrit. 2; H315. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411.	25 - 50 %
EC No. 232-455-8 CAS 8042-47-5	White mineral oil (petroleum) Asp. Tox. 1; H304.	5 - 10 %
EC No. 227-813-5 CAS 5989-27-5	(R)-p-Mentha-1,8-diene Flam. Liq. 3; H226. Skin Irrit. 2; H315. Skin Sens. 1B; H317. Asp. Tox. 1; H304. Aquatic Acute 1; H400. Aquatic Chronic 1; H410. M-factors: Aquatic Acute 1: M = 1.	< 1 %
EC No. 204-696-9 CAS 124-38-9	Carbon dioxide Press. Gas (Liq.); H280.	2.5 - 5 %



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. May cause allergic reactions in already sensitized persons.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Extinguishing powder, Sand, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. May form dangerous gases and vapours in case of fire. Furthermore, there may develop: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Hazchem-Code: -

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:6/6/2023Version:1.4Replaces version:1.3Language:en-GBDate of print:7/6/2023Page:4 of 11

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours/spray. Avoid contact with the substance. In case of leakage, eliminate all ignition sources. Provide adequate ventilation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away. Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

ERNE

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling:Provide adequate ventilation, and local exhaust as needed. Avoid breathing vapours/spray. Do
not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply
emergency spray.Precautions against fire and explosion:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition
source.

7.2 Conditions for safe storage, including any incompatibilities

 Requirements for storerooms and containers:
 Keep container tightly closed and in a well-ventilated place.

 Keep container dry. Keep only in the original container.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

 Store containers in upright position.
 Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:6/6/2023Version:1.4Replaces version:1.3Language:en-GBDate of print:7/6/2023Page:5 of 11

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

BERNER

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
109-66-0	Pentane	Great Britain: WEL-TWA	1800 mg/m³; 600 ppm
64742-49-0	Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Great Britain: WEL-TWA	1800 mg/m³ (C5-C6 alkenes)
124-38-9	Carbon dioxide	Great Britain: WEL-STEL Great Britain: WEL-TWA	27400 mg/m³; 15000 ppm 9150 mg/m³; 5000 ppm

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

Respiratory protection:	Respiratory protection must be worn whenever the WEL levels have been exceeded. Recommendation: Use filter type AX (= against vapours of low boiling organic substances) according to EN 14387. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection:	Protective gloves according to EN 374. Glove material: Nitrile rubber - Layer thickness: > 0.68 mm. Breakthrough time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to BS EN ISO 16321-1:2022.
Body protection:	Flame retardant, antistatic and chemical resistant protective clothing.
General protection and hygien	
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing vapours/spray. Do not get in eyes, on skin, or on clothing. When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.
	emergency spray.

Environmental exposure controls

See subsection 6.2

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol Colour: Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH:	Not determined



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:	6/6/2023
Version:	1.4
Replaces vers	ion: 1.3
Language:	en-GB
Date of print:	7/6/2023
Page:	6 of 11

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	<= 35 °C
Flash point/flash point range:	-20 °C
Evaporation rate:	Not applicable
Flammability:	Extremely flammable aerosol.
Explosion limits:	LEL (Lower Explosion Limit): Not determined
	UEL (Upper Explosive Limit): Not determined
Vapour pressure:	Not determined
Vapour density:	Not determined
Density:	at 20 °C: 0.63 g/mL
Water solubility:	Slightly miscible
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	Not self-igniting
Decomposition temperature:	No data available
Viscosity, dynamic:	Not determined
Viscosity, kinematic:	Not determined
Explosive properties:	Product is not explosive. Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available
0.2 Other information	

9.2 Other information

Additional information:

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

 No decomposition when used properly.

 Thermal decomposition:
 No data available

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:6/6/2023Version:1.4Replaces version:1.3Language:en-GBDate of print:7/6/2023Page:7 of 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

BERNER

Toxicological effects:	The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
	Acute toxicity (oral): Based on available data, the classification criteria are not met.
	Acute toxicity (dermal): Based on available data, the classification criteria are not met.
	Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
	Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.
	Serious eye damage/irritation: Based on available data, the classification criteria are not met.
	Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.
	Skin sensitisation: Based on available data, the classification criteria are not met. Contains (R)-p-Mentha-1,8-diene. May produce an allergic reaction.
	Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.
	Carcinogenicity: Based on available data, the classification criteria are not met.
	Reproductive toxicity: Based on available data, the classification criteria are not met.
	Effects on or via lactation: Lack of data.
	Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.
	Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.
	Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.
Other information:	Information about (R)-p-Mentha-1,8-diene: LD50 Rat, oral: 4,400 mg/kg
Symptoms	
	Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect. After contact with skin: The product is skin resorptive. After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:Toxic to aquatic life with long lasting effects.Information about Hydrocarbons, C6, isoalkanes, < 5% n-hexane:
Fish toxicity:
LC50 Oncorhynchus mykiss: 18.27 mg/L/96h
NOEC Oncorhynchus mykiss: 4.089 mg/L/28d
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 31.9 mg/L/48h
NOEC Daphnia magna (Big water flea): 7.138 mg/L/21d
Information about (R)-p-Mentha-1,8-diene:
Algae toxicity: EC50: 0.32 mg/L

12.2 Persistence and degradability

Further details:

No data available



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:	6/6/2023
Version:	1.4
Replaces vers	ion: 1.3
Language:	en-GB
Date of print:	7/6/2023
Page:	8 of 11

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

Not determined

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

TTOULOL	
Waste key number:	 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances/Aerosol * = Evidence for disposal must be provided.
Recommendation:	Do not pierce or burn, even after use.
	Special waste. Dispose of waste according to applicable legislation. Do not dispose of with household waste.
Package	
Waste key number:	 15 01 10* = packaging containing residues of or contaminated by dangerous substances * = Evidence for disposal must be provided.
Recommendation:	Dispose of waste according to applicable legislation. Empty carefully and completely, if possible. Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR: UN 1950

14.2 UN proper shipping name

ADR/RID:	UN 1950, AEROSOLS
IMDG:	UN 1950, AEROSOLS (Pentane; Hydrocarbons, C6, isoalkanes, < 5% n-hexane),
	MARINE POLLUTANT
IATA-DGR:	UN 1950, AEROSOLS, FLAMMABLE



SAFETY DATA SHEET according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date:	6/6/2023
Version:	1.4
Replaces vers	ion: 1.3
Language:	en-GB
Date of print:	7/6/2023
Page:	9 of 11

14.3 Transport hazard class(es)

ADR/RID:	Class 2, Code: 5F
IMDG:	Class 2.1, Subrisk -
IATA-DGR:	Class 2.1

14.4 Packing group

ADR/RID, IATA-DGR: IMDG:

14.5 Environmental hazards

Marine pollutant:

yes

not applicable

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board:	RID: Kemmler-number 23, UN number UN 1950
Hazard label:	2.1
Special Provisions:	190 327 344 625
Limited quantities:	1 L
EQ:	E0
Package - Instructions:	P207 LP200
Package - Special Provisions:	PP87 RR6 L2
Special provisions for packing together:	MP9
Tunnel restriction code:	D
Sea transport (IMDG)	

Sea transport (I JG)

EmS:	F-D, S-U
Special Provisions:	63 190 277 327 344 381 959
Limited quantities:	1000 mL
Excepted quantities:	E0
Package - Instructions:	P207, LP200
Package - Provisions:	PP87, L2
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	SW1 SW22
Segregation:	SG69
Properties and observations:	-
Segregation group:	none

Air transport (IATA)

Hazard label:	Flamm. gas
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions:	A145 A167 A802
Emergency Response Guide-Code (ERG):	10L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available



ccording to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date: 6/6/2023 Version: 1.4 Replaces version: 1.3 Language: en-GB Date of print: 7/6/2023 Page:

10 of 11

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

ERNE

Hazchem-Code:

No data available

National regulations - EC member states

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg Environmental hazards: Code E2, Quantity threshold 200 000 kg / 500 000 kg Use restriction according to REACH annex XVII, no.: 3, 40, 75 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H222 = Extremely flammable aerosol.

[Seveso-III-Directive]: P3b, E2

H225 = Highly flammable liquid and vapour.

H226 = Flammable liquid and vapour.

H229 = Pressurised container: May burst if heated.

H280 = Contains gas under pressure; may explode if heated.

H304 = May be fatal if swallowed and enters airways.

H315 = Causes skin irritation.

H317 = May cause an allergic skin reaction.

H336 = May cause drowsiness or dizziness.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

H411 = Toxic to aquatic life with long lasting effects.

EUH066 = Repeated exposure may cause skin dryness or cracking.

EUH208 = Contains (R)-p-Mentha-1,8-diene. May produce an allergic reaction.



SAFETY DATA SHEET according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Electronic spray

Revision date: 6/6/2023 Version: 1.4 1.3 Replaces version: Language: en-GB Date of print: 7/6/2023 Page: 11 of 11

Abbreviations and acronyms:	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road Aerosoi: Aerosoi Aquatic Acute: Hazardous to the aquatic environment - acute Aquatic Chronic: Hazardous to the aquatic environment - chronic ASINZS: Australian Standards/New Zealand Standards Asp. Tox: Aspiration toxicity CAS: Chemical Abstracts Service CFR: Code of Federal Regulations CLP: Classification, Labelling and Packaging DME:: Derived noi-effect level DNE:: Derived noi-effect level EC: European Community EC:50: Effective Concentration 50% EN: European Natardards/New Zealand Standards EU: European Community EC:50: Effective Concentration 50% EN: European Otion Flam. Lq.: Flammable liquid IATA: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Maritime Dangerous Goods Code LO50: Median lethal concentration LD50: Lethal dose 50% LEI: Lower Explosion Limit MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships M-factor: Multiplication factor NOEC: No Observed Effect Concentration PET: Persistent, bioaccumulative and toxic PHEC: Predicted no-effect ancentration PHEC: Predicted no-effect ancentra
Reason of change:	WEL: Workplace Exposure Limit Changes in section 14: General revision
Date of first version:	31/3/2021

Department issuing data sheet

Contact person:

see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.