

Page 1 of 32
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2021 / 0013
Replacing version dated / version: 11.01.2021 / 0012
Valid from: 28.04.2021
PDF print date: 24.06.2021
Primer Plast-O-Fix 150 ml
Art.: 409841

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Primer Plast-O-Fix 150 ml
Art.: 409841

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Primer/adhesion promoter

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coatings and paints, thinners, paint removers

PC35 - Washing and cleaning products

Process category [PROC]:

PROC10 - Roller application or brushing

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Berner Produkten b.v.

Steenbergstraat 25

6465 AB Kerkrade

Tel.: +31 45 53 39 133

Web: www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Page 2 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 221 80260 889 (9:00h - 17:00h)

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.
P261-Avoid breathing vapours or spray. P280-Wear eye protection.
P312-Call a POISON CENTRE / doctor if you feel unwell.
P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Page 3 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Without adequate ventilation, formation of explosive mixtures may be possible.
 n-butyl acetate
 Ethyl acetate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 Dangerous vapours heavier than air.
 In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Ethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475103-46-XXXX
Index	607-022-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4
CAS	141-78-6
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119485493-29-XXXX
Index	607-025-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	204-658-1
CAS	123-86-4
content %	1-15
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 STOT SE 3, H336
Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	1-<10

Page 4 of 32
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2021 / 0013
Replacing version dated / version: 11.01.2021 / 0012
Valid from: 28.04.2021
PDF print date: 24.06.2021
Primer Plast-O-Fix 150 ml
Art.: 409841

**Classification according to Regulation (EC)
1272/2008 (CLP), M-factors**

Flam. Liq. 3, H226
Asp. Tox. 1, H304
Acute Tox. 4, H312
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Acute Tox. 4, H332
STOT SE 3, H335
STOT RE 2, H373

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.
Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Product removes fat.

Dermatitis (skin inflammation)

Drying of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Room ventilation also at ground level.

Avoid inhalation of the vapours.

GB

Page 6 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Avoid contact with eyes or skin.
 Keep away from sources of ignition - Do not smoke.
 Take precautions against electrostatic charges.
 Do not use on hot surfaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Store cool.
 Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name		Ethyl acetate	Content %: 25-50
WEL-TWA: 200 ppm (734 mg/m3) (WEL, EU)	WEL-STEL: 400 ppm (1468 mg/m3) (WEL, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Ethyl Acetate 200/a (CH 20 201) - Compur - KITA-111 SA (549 160) - Compur - KITA-111 U(C) (549 178) - DFG Meth. Nr. 1 (D) (Lösungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1993, 2002 - DFG Meth. Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2014, 2002 - NIOSH 1457 (ETHYL ACETATE) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 		
BMGV: ---	Other information: ---		
Chemical Name		n-butyl acetate	Content %: 1-15
WEL-TWA: 150 ppm (724 mg/m3) (WEL), 50 ppm (241 mg/m3) (EU)	WEL-STEL: 200 ppm (966 mg/m3) (WEL), 150 ppm (723 mg/m3) (EU)	---	

GB

Page 7 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Monitoring procedures:

- Compur - KITA-138 U (548 857)
- Compur - KITA-139 SB(C) (549 731)
- NIOSH 1450 (ESTERS 1) - 2003
- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007

BMGV: --- Other information: ---

Chemical Name	Xylene	Content %: 1-<10
WEL-TWA: 220 mg/m ³ (50 ppm) (WEL), 50 ppm (221 mg/m ³) (EU)	WEL-STEL: 100 ppm (441 mg/m ³) (WEL), 100 ppm (442 mg/m ³) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Xylene 10/a (67 33 161) - Compur - KITA-143 SA (550 325) - Compur - KITA-143 SB (505 998) - INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999 	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	

Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993 	
BMGV: ---	Other information: ---	

Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990 	
BMGV: ---	Other information: ---	

Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-113 SB(C) (549 368) 	
BMGV: ---	Other information: ---	

Ethyl acetate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - marine		PNEC	0,024	mg/l	

GB

Page 8 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

	Environment - water, sporadic (intermittent) release		PNEC	1,65	mg/l	
	Environment - sediment, freshwater		PNEC	1,15	mg/kg	
	Environment - sediment, marine		PNEC	0,115	mg/kg	
	Environment - soil		PNEC	0,148	mg/kg	
	Environment - sewage treatment plant		PNEC	650	mg/l	
	Environment - oral (animal feed)		PNEC	200	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	37	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	367	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	734	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m3	

n-butyl acetate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,18	mg/l	
	Environment - marine		PNEC	0,018	mg/l	
	Environment - periodic release		PNEC	0,36	mg/l	
	Environment - sediment, freshwater		PNEC	0,981	mg/kg	
	Environment - sediment, marine		PNEC	0,098 1	mg/kg	
	Environment - soil		PNEC	0,090 3	mg/kg	

GB

Page 9 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

	Environment - sewage treatment plant		PNEC	35,6	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3,4	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	300	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35,7	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	300	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	35,7	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	600	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	300	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	7	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	600	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	300	mg/m3	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	



Page 10 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	65,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	221	mg/m3	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Page 11 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective gloves in butyl rubber (EN 374).

Permeation time (penetration time) in minutes:

With short-term contact:

> 120

With long-term contact:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	n.a.
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,5 Vol-%
Upper explosive limit:	11,5 Vol-%
Vapour pressure:	830 kPa (20°C)
Vapour density (air = 1):	n.a.
Density:	0,77 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	n.a.
Decomposition temperature:	n.a.
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

GB

Page 13 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Pressure increase will result in danger of bursting.
 Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Primer Plast-O-Fix 150 ml
Art.: 409841

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4 h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4 h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Ethyl acetate

GB

Page 14 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4 h	Rat		Vapours
Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No

GB

Page 15 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Symptoms:						lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting, fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

n-butyl acetate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10760	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>14112	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

GB

Page 16 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Acute toxicity, by inhalation:	LC50	21,1	mg/l/4 h	Rat	OECD 403 (Acute Inhalation Toxicity)	Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEC	9640	mg/m3		OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Symptoms:						drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	500	ppm	Rat		
Other information:						Repeated exposure may cause skin dryness or cracking.

Xylene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

GB

Page 17 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification
Acute toxicity, by inhalation:	LC50	29,09	mg/l/4 h	Rat	Regulation (EC) 440/2008 B.2 (ACUTE TOXICITY (INHALATION))	Vapours, Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Irritant
Serious eye damage/irritation:				Rabbit		Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative
Carcinogenicity:	NOAEL	500	mg/kg	Rat		
Reproductive toxicity (Developmental toxicity):	NOAEL	2,171	mg/l	Rat		
Reproductive toxicity (Effects on fertility):	NOAEC	0,868	mg/l	Rat		

GB

Page 18 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness, burning of the membranes of the nose and throat, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea and vomiting., lack of appetite
-----------	--	--	--	--	--	--

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No

GB

Page 19 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

GB

Page 20 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Aspiration hazard: Symptoms:						No breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

Isobutane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

GB

Page 21 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Primer Plast-O-Fix 150 ml Art.: 409841

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50		> 50	mg/l			
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Toxicity to bacteria:	EC50		> 100	mg/l			
Other information:							According to the recipe, contains no AOX.

Ethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

GB

Page 22 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Toxicity to bacteria:	EC10	18h	2900	mg/l	<i>Pseudomonas putida</i>		
12.1. Toxicity to fish:	LC50	48h	333	mg/l	<i>Leuciscus idus</i>		
12.1. Toxicity to fish:	NOEC/NOEL	32d	>9,65	mg/l	<i>Pimephales promelas</i>		
12.1. Toxicity to fish:	LC50	96h	230	mg/l	<i>Pimephales promelas</i>		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	<i>Daphnia magna</i>	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,4	mg/l	<i>Daphnia magna</i>	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	165	mg/l			<i>Daphnia cucullata</i>
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	<i>Desmodesmus subspicatus</i>	DIN 38412 T.9	
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	<i>Scenedesmus subspicatus</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	<i>Pseudokirchneriella subcapitata</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	<i>Desmodesmus subspicatus</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	48h	3300	mg/l	<i>Scenedesmus subspicatus</i>		
12.2. Persistence and degradability:		20d	79	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	72h	30				(Fish)
12.3. Bioaccumulative potential:	Log Kow		0,68			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1). 25 °C
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m ³ /mol			

GB

Page 23 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium phosphoreum		

n-butyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.6. Other adverse effects:							Product floats on the water surface.
12.3. Bioaccumulative potential:	BCF		15,3				
12.1. Toxicity to fish:	LC50	96h	18	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	44	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	23	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	397	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		28d	98	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,81-2,3				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

GB

Page 24 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Toxicity to bacteria:	EC10		959	mg/l	Pseudomonas putida		
-----------------------	------	--	-----	------	--------------------	--	--

Xylene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.4. Mobility in soil:	Log Koc		2,73				
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	56d	>1,3	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	1,17	mg/l	Ceriodaphnia spec.	U.S. EPA-600/4-91-003	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to daphnia:	IC50	24h	1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.3. Bioaccumulative potential:	Log Pow		2,77-3,2				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.3. Bioaccumulative potential:	BCF		>5,5 - 25,9				
12.1. Toxicity to algae:	EC50	72h	2,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,44	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.4. Mobility in soil:	H (Henry)		623-665	Pa*m ³ /mol			

GB

Page 25 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

Toxicity to bacteria:	NOEC/NOEL	3h	157	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

GB

Page 26 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS



GB

Page 27 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 Classification code: 5F
 LQ: 1 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name: AEROSOLS
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: n.a
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name: Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements

GB

Page 28 of 32
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2021 / 0013
 Replacing version dated / version: 11.01.2021 / 0012
 Valid from: 28.04.2021
 PDF print date: 24.06.2021
 Primer Plast-O-Fix 150 ml
 Art.: 409841

P3a	11.1	150 (netto)	500 (netto)
-----	------	-------------	-------------

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 98,5 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.



Page 29 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Acute Tox. — Acute toxicity - dermal

Skin Irrit. — Skin irritation

Acute Tox. — Acute toxicity - inhalation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

STOT RE — Specific target organ toxicity - repeated exposure

Albert Berner Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
www.berner.de

Berner Gesellschaft m.b.H.
Industriezeile 36
A - 5280 Braunau am Inn
Tel +43 77 22 80 00
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
3620 Lanaken
Zweigniederlassung:
105B, Rue des Bruyères
1274 Howald
Luxembourg

Montagetechnik Berner AG
Kägenstraße 8
4153 Reinach BL 1

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
www.berner.dk

Berner, Montaje y Fijación, S.L.
Poligono Industrial "La Rosa" VI
C/Albert Berner, núm. 2
E-18330 Chauchina-Granada
Tel +34 (0) 958 060-200
www.berner.es

Berner KFT
Gubacsi út 6/B
1097 Budapest

Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 7655-80
www.berner.no

Berner spol. s r.o.
Jinonická 80
CZ - 15800 Praha 5 Košiče

Page 30 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

Berner S.A., Edificio Berner
Av. Amália Rodrigues,3510
Manique de Baixo
P-2785-738 São Domingos de
Rana

UAB Albert Berner
K. Ladygos str. 1
LT-08235 Vilnius
Tel +370 (0) 52 10 43 55
www.berner.lt

Berner s.r.o.
Jesenského 1
96212 Detva

Albert Berner Montageteknik AB
Elektravägen 53
S-126 30 Hägersten
Tel +46 (0) 85 78 77 800
www.berner.se

BERNER d.o.o
CPM Savica Sancj
Majstorska 9
10000 Zagreb

Berner S.p.A.
Via dell 'Elettronica, 15
I - 37139 Verona
Tel +39 04 58 67 01 11
www.berner.it

Albert Berner S.R.L.
Str. Vrancei Nr. 51 - 55
310315 Arad

Berner Produkten b.v.
Steenbergstraat 25
6654 AB Kerkrade
+31 45 53 39 133
www.berner.nl

Berner Logistics Kerkrade B.V.
Steenbergstraat 25
6465 AB Kerkrade

Berner s.a.r.l.
14, rue Albert Berner
Z.I. Les Manteaux
F - 89331 Saint-Julien-du-Sault
Cedex
Tel +33 38 69 94 400
www.berner.fr

Berner Holding France SAS
37, rue de Liège
75008 Paris

Berner Industry Services
37, rue de Liège
75008 Paris

SIA Albert Berner
Liliju iela 20
LV-2167 Marupe, Rigas raj.
Tel +371 (0) 67 84 00 07
www.berner.lv

Berner Polska Spółka z o.o.
Ul. Puzkarska 7j
PL-30-644 Kraków
Tel +48 12 297 62 00
www.berner.pl

(c) COPYRIGHT 1987 - 2050 ALL
RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

Page 31 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

GB

Page 32 of 32

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2021 / 0013

Replacing version dated / version: 11.01.2021 / 0012

Valid from: 28.04.2021

PDF print date: 24.06.2021

Primer Plast-O-Fix 150 ml

Art.: 409841

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.:

+49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.